



Common Specification Of Steel Grating	
Material Standard	ASTM A36, A1011, A569, Q235, S275JR, Stainless steel 304, Mild steel & Low carbon steel, etc
Bearing Bar (width*thickness)	25x3, 25x4, 25x4.5, 25x5, 30x3, 30x4, 30x4.5, 30x5, 32x5, 40x5, 50x5, 65x5, 75x6, 75x10.....100 x10mm etc; I bar: 25x5x3, 30x5x3, 32x5x3, 40x5x3 etc US standard: 1"x3/16", 1 1/4"x3/16", 1 1/2"x3/16", 1"x1/4", 1 1/4"x1/4", 1 1/2"x1/4", 1"x1/8", 1 1/4"x1/8", 1 1/2"x1/8" etc
Bearing Bar Pitch	12.5, 15, 20, 23.85, 25, 30, 30.16, 30.3, 32.5, 34.3, 35, 38.1, 40, 41.25, 60, 80mm etc. US standard: 19-w-4, 15-w-4, 11-w-4, 19-w-2, 15-w-2 etc.
Twisted Cross Bar Pitch	38.1, 50, 60, 76, 80, 100, 101.6, 120mm, 2" & 4" etc
Surface treatment	untreated(black), hot-dipped galvanized, powder coated, electroplate, painting or as per customers' requirement.
Grating Style	Plain / Smooth, Serrated /teeth, I bar, serrated I bar