

Specifications of plain weave or twill weave black woven wire mesh.

Mesh/Inch	Opening (mm)	Wire Diameter (mm)	Reference weight (kg/sq. meter)
10 mesh × 10 mesh	1.94	0.6	1.8
10 mesh × 10 mesh	1.98	0.56	1.56
12 mesh × 12 mesh	1.52	0.6	2.16
12 mesh × 12 mesh	1.56	0.56	1.88
18 mesh × 18 mesh	0.96	0.45	1.82
18 mesh × 18 mesh	1.0	0.41	1.52
18 mesh × 18 mesh	1.04	0.37	1.23
18 mesh × 18 mesh	1.06	0.35	1.1
20 mesh × 20 mesh	0.86	0.41	1.68
20 mesh × 20 mesh	0.9	0.37	1.38
22 mesh × 22 mesh	0.74	0.35	1.33
22 mesh × 22 mesh	0.79	0.30	0.99
24 mesh × 24 mesh	0.7	0.35	1.5
26 mesh × 26 mesh	0.63	0.35	1.66
28 mesh × 28 mesh	0.6	0.31	1.36
30 mesh × 30 mesh	0.64	0.31	1.46
32 mesh × 32 mesh	0.5	0.29	1.36
34 mesh × 34 mesh	0.47	0.28	1.3
36 mesh × 36 mesh	0.47	0.28	1.3
38 mesh × 38 mesh	0.41	0.26	1.1
40 mesh × 40 mesh	0.39	0.25	1.2
40 mesh × 40 mesh	0.41	0.23	1.06
40 mesh × 40 mesh	0.43	0.21	0.88
42 mesh × 42 mesh	0.365	0.24	1.1
44 mesh × 44 mesh	0.347	0.23	1.0
46 mesh × 46 mesh	0.332	0.22	1.0
48 mesh × 48 mesh	0.319	0.20	0.96
50 mesh × 50 mesh	0.318	0.19	0.91
50 mesh × 50 mesh	0.338	0.17	0.72
56 mesh × 56 mesh	0.248	0.17	0.81

60 mesh × 60 mesh	0.27	0.15	0.68
-------------------	------	------	------

Specification sheet of dutch weave black woven wire mesh.

Mesh/Inch	Wire diameter (mm)
12 × 64	0.58/ 0.64
14 × 88	0.50/ 0.33
24 × 110	0.36/ 0.25
30 × 150	0.23/ 0.18
40 × 200	0.18/ 0.13

Note: Special size and specifications can be made according to customers requires.