








Specifications of Razor wire				
The Coil Diameter	No. of loops	Length per coil	Razor Wire Types	Notes
450mm	33	7-8m	CBT-60.65	single coil
500mm	56	12-13m	CBT-60.65	single coil
700mm	56	13-14m	CBT-60.65	single coil
960mm	56	14-15m	CBT-60.65	single coil
450mm	56	8-9m(3 clips)	BTO-10.12.18.22.28.3 0	cross type
500mm	56	9-10m (3clips)	BTO-10.12.18.22.28.3 0	cross type
600mm	56	10-11M (3 clips)	BTO-10.12.18.22.28.3 0	cross type
600mm	56	8-10M (5clips)	BTO-10.12.18.22.28.3 0	cross type
700mm	56	8-10M (5 clips)	BTO-10.12.18.22.28.3 0	cross type
800mm	56	11-13M (5 clips)	BTO-10.12.18.22.28.3 0	cross type
900mm	56	12-14M (5 clips)	BTO-10.12.18.22.28.3 0	cross type
960mm	56	13-15M (5 clips)	BTO-10.12.18.22.28.3 0	cross type
960mm	56	14-16M (5 clips)	BTO-10.12.18.22.28.30	

Note: Special size and specifications can be made according to customers requires.

Reference Number	Blade Style	Thickness	Wire Dia	Barb Length	Barb Width	Barb spacing
BTO-12		0.5±0.05	2.5±0.1	12±1	15±1	26±1
BTO-15		0.5±0.05	2.5±0.1	15±1	15±1	33±1
BTO-22		0.5±0.05	2.5±0.1	22±1	15±1	34±1
BTO-25		0.5±0.05	2.5±0.1	25±1	16±1	40±1
BTO-30		0.5±0.05	2.5±0.1	30±1	18±1	45±1
CBT-60		0.6±0.05	2.5±0.1	60±2	32±1	100±2
CBT-65		0.6±0.05	2.5±0.1	65±2	21±1	100±2